



DIN Compression Cable Lugs

Features

- Manufactured according to DIN 46235
- With marking for correct crimping

Material

- E-Cu

Surface

- Tin plated

Part No.	Item	Cross Section mm ²	Size of Bolt Φ	Dimensions(mm)				
				D	d	a	b	L
A01011	DCL 6-5	6	M 5	5.5	3.8	10.0	8.5	30.5
A01012	DCL 6-6		M 6	5.5	3.8	10.0	8.5	31.5
A01013	DCL 6-8		M 8	5.5	3.8	10.0	13.0	34.0
A01014	DCL 10-5	10	M 5	6.0	4.5	10.0	9.0	34.0
A01015	DCL 10-6		M 6	6.0	4.5	10.0	9.0	34.5
A01016	DCL 10-8		M 8	6.0	4.5	10.0	13.0	37.0
A01017	DCL 10-10	16	M 10	6.0	4.5	10.0	15.0	39.0
A01018	DCL 16-6		M 10	8.5	5.5	20.0	13.0	43.5
A01019	DCL 16-8		M 8	8.5	5.5	20.0	13.0	46.0
A010110	DCL 16-10	25	M 10	8.5	5.5	20.0	17.0	48.0
A010111	DCL 16-12		M 12	8.5	5.5	20.0	18.0	49.0
A010112	DCL 25-6		M 6	10.0	7.0	20.0	14.0	45.5
A010113	DCL 25-8	35	M 8	10.0	7.0	20.0	16.0	48.0
A010114	DCL 25-10		M 10	10.0	7.0	20.0	17.0	50.0
A010115	DCL 25-12		M 12	10.0	7.0	20.0	19.0	51.0
A010116	DCL 35-6	50	M 6	12.5	8.2	20.0	17.0	49.5
A010117	DCL 35-8		M 8	12.5	8.2	20.0	17.0	52.0
A010118	DCL 35-10		M 10	12.5	8.2	20.0	19.0	54.0
A010119	DCL 35-12	70	M 12	12.5	8.2	20.0	21.0	55.0
A010120	DCL 35-14		M 14	12.5	8.2	20.0	21.0	56.5
A010121	DCL 50-8		M 8	14.5	10.0	28.0	20.0	62.0
A010122	DCL 50-10	70	M 10	14.5	10.0	28.0	22.0	64.0
A010123	DCL 50-12		M 12	14.5	10.0	28.0	24.0	65.0
A010124	DCL 50-14		M 14	14.5	10.0	28.0	24.0	66.5
A010125	DCL 50-16	70	M 16	14.5	10.0	28.0	28.0	68.0
A010126	DCL 70-8		M 8	16.5	11.5	28.0	24.0	65.0
A010127	DCL 70-10		M 10	16.5	11.5	28.0	24.0	67.0
A010128	DCL 70-12	70	M 12	16.5	11.5	28.0	24.0	68.0
A010129	DCL 70-14		M 14	16.5	11.5	28.0	24.0	69.5
A010130	DCL 70-16		M 16	16.5	11.5	28.0	30.0	71.0

DIN Compression Cable Lugs

Part No.	Item	Cross Section mm ²	Size of Bolt Φ	Dimensions(mm)				
				D	d	a	b	L
A010131	DCL 95-8	95	M 8	19.0	13.5	35.0	28.0	77.0
A010132	DCL 95-10		M 10	19.0	13.5	35.0	28.0	77.0
A010133	DCL 95-12		M 12	19.0	13.5	35.0	28.0	78.0
A010134	DCL 95-14		M 14	19.0	13.5	35.0	28.0	79.5
A010135	DCL 95-16	120	M 16	19.0	13.5	35.0	32.0	81.0
A010136	DCL 120-10		M 10	21.0	15.5	35.0	32.0	85.0
A010137	DCL 120-12		M 12	21.0	15.5	35.0	32.0	86.0
A010138	DCL 120-14		M 14	21.0	15.5	35.0	32.0	88.0
A010139	DCL 120-16	150	M 16	21.0	15.5	35.0	32.0	89.0
A010140	DCL 120-20		M 20	21.0	15.5	35.0	38.0	91.0
A010141	DCL 150-10		M 10	23.5	17.0	35.0	34.0	93.0
A010142	DCL 150-12		M 12	23.5	17.0	35.0	34.0	94.0
A010143	DCL 150-14	185	M 14	23.5	17.0	35.0	34.0	97.0
A010144	DCL 150-16		M 16	23.5	17.0	35.0	34.0	97.0
A010145	DCL 150-20		M 20	23.5	17.0	35.0	40.0	99.0
A010146	DCL 185-10		M 10	25.5	19.0	40.0	37.0	97.0
A010147	DCL 185-12	240	M 12	25.5	19.0	40.0	37.0	98.0
A010148	DCL 185-14		M 14	25.5	19.0	40.0	37.0	101.0
A010149	DCL 185-16		M 16	25.5	19.0	40.0	37.0	101.0
A010150	DCL 185-20		M 20	25.5	19.0	40.0	40.0	103.0
A010151	DCL 240-12	300	M 12	29.0	21.5	40.0	42.0	108.0
A010152	DCL 240-14		M 14	29.0	21.5	40.0	42.0	111.0
A010153	DCL 240-16		M 16	29.0	21.5	40.0	42.0	111.0
A010154	DCL 240-20		M 20	29.0	21.5	40.0	45.0	113.0
A010155	DCL 300-12	400	M 12	32.0	24.5	50.0	46.0	119.0
A010156	DCL 300-14		M 14	32.0	24.5	50.0	46.0	119.0
A010157	DCL 300-16		M 16	32.0	24.5	50.0	46.0	119.0
A010158	DCL 300-20		M 20	32.0	24.5	50.0	46.0	122.0
A010159	DCL 400-14	500	M 14	38.5	27.5	70.0	55.0	140.0
A010160	DCL 400-16		M 16	38.5	27.5	70.0	55.0	140.0
A010161	DCL 400-20		M 20	38.5	27.5	70.0	55.0	140.0
A010162	DCL 500-16		M 16	42.0	31.0	70.0	60.0	150.0
A010163	DCL 500-20	630	M 20	42.0	31.0	70.0	60.0	150.0
A010164	DCL 625-16		M 16	44.0	34.5	80.0	64.0	160.0
A010165	DCL 625-20		M 20	44.0	34.5	80.0	64.0	160.0
A010166	DCL 800-16		M 16	52.0	40.0	100.0	75.0	195.0
A010167	DCL 800-20	800	M 20	52.0	40.0	100.0	75.0	195.0
A010168	DCL 1000-16		M 16	58.0	44.0	100.0	85.0	195.0
A010169	DCL 1000-20		M 20	58.0	44.0	100.0	85.0	195.0